

PMXCITE®

CLEAN, BOLD LINES AND ULTRA-LIGHT FRAME



PART

SB7710D***


SB7718D***

SB7720D***

SB7721D**

SB7770D**

LENS

 Clear

 Sandstone Bronze

 Gray

 Gray Polarized

 Silver Mirror

- Adjustable rubber nose piece.
- Lenses provide 99.9% protection against harmful UV rays.
- Clean, bold lines and ultra-light frame provide all-day versatility.
- Dual-injected rubber temple tips generate a soft cushion for comfort behind the ear.
- Lightweight frame is vented at the top of the lens, allowing air to circulate away from the user's face and prevent fogging.

GENERAL SPECIFICATION

Bridge: 10mm

Closest Point Between Lens: 17.5mm

Closest Point Between Temple Tips: 99mm

Lens Base: 9 Curve

Lens Size Diagonal: 72mm

Lens Size Vertical: 41.3mm

Lens Thickness: 2.3mm

Overall Length (Lens-Tip): 160mm

Overall Width (Hinge-Hinge): 136mm

PD: 68mm

Weight: 25gm

PACKAGING

Polybag: 1pc






Inner Box: 12 pcs

Case: 300 pcs

PMXCITE®

CLEAN, BOLD LINES AND ULTRA-LIGHT FRAME

COMPONENT	MATERIAL	FEATURES
Hinge	Polycarbonate	3 barrel type
Lens	Polycarbonate	9 base wrap around lens
Temple	Polycarbonate/Nylon	Co-injected soft temple tips for comfort
Temple Tip	TPE	
Side Shields	Polycarbonate	Wide temples replace the S.S function
Screw	Stainless Steel	Standard hinge screw
Frame	Nylon	Dual frame type
Nose Piece	PVC	Soft nose pad slips on metal insert, adjustable for customized fit
	Copper / Brass Alloy	

PART	LENS	LENS MARKING	FRAME MARKING
SB7710D	 Clear	P Z87 + U6	P Z87 +
SB7718D	 Sandstone Bronze	P Z87 + S	P Z87 +
SB7720D	 Gray	P Z87 + U6 L2.5	P Z87 +
SB7721D	 Gray Polarized	P Z87 + S	P Z87 +
SB7770D	 Silver Mirror	P Z87 + S	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact