

MINI INTRUDER®

DESIGNED FOR SMALLER FACIAL FEATURES



PART	LENS
S4110SN**	<input type="checkbox"/> Clear
S4110SNT*	<input type="checkbox"/> Clear (Anti-Fog)
S4120SN*	<input checked="" type="checkbox"/> Gray
S4180SN*	<input type="checkbox"/> Indoor/Outdoor Mirror

- Superior comfort and fit.
- Lightweight, frameless protection is ideal for all-day wear.
- Mini Intruder has all the great features of Intruder in a design better suited for smaller facial sizes.
- Coated lens provides excellent side protection and 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 14.17mm
Closest Point Between Lens: 14.38mm
Closest Point Between Temples: 77.83mm
Lens Base: 11 curve
Lens Size Diagonal: 69.43mm
Lens Size Vertical: 39.92
Lens Thickness: 2.1mm
Overall Length (Lens-Tip): 144mm
Overall Width (Hinge-Hinge): 121.8mm
PD: 62mm
Weight: 17.9g

MINI INTRUDER®

DESIGNED FOR SMALLER FACIAL FEATURES





PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 base curve
Temple	Polycarbonate	Straight
Hinge	Polycarbonate	Integral to temples
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S4110SN	 Clear	P Z87 + H U6	P Z87 +
S4110SNT	 Clear (Anti-Fog)	P Z87 + H U6	P Z87 +
S4120SN	 Gray	P Z87 + H U6 L3	P Z87 +
S4180SN	 Indoor/Outdoor Mirror	P Z87 + H U6 L1.7	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact