






ROTATOR®

ALL-DAY VERSATILITY



PART	LENS
SB7810S*	 Clear
SB7820S*	 Gray
SB7830S*	 Amber
SB7870S*	 Silver Mirror
SB7880S*	 Indoor/Outdoor Mirror

- Provides 99% protection against harmful UV rays.
- Maximum eye protection, and ultra-light design ideal for all-day versatility.
- Wrap-around, single lens design, with high quality optics provides a clear panoramic view without obstruction.
- Thin, soft flange of the extra wide nosepiece distributes weight of the glass evenly across the bridge, eliminating pressure on the nose.
- Flexible rubber temples generate a soft cushion for pressure-free fit behind the ear, and secure the eyewear from shifting out of place.
- To take up minimal space in your pocket or vehicle, the temples rotate to a compact, closed position, making the safety eyewear easy to store.

GENERAL SPECIFICATION

Bridge: 17.2mm
Closest Point Between Lens: N/A
Closest Point Between Temple Tips: 20mm
Lens Base: 6.5 curve
Lens Size Diagonal: 145.2mm
Lens Size Vertical: 50.6mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 143.5mm
Overall Width (Hinge-Hinge): 139.5mm
PD: 68mm
Weight: 28gm






ROTATOR®

ALL-DAY VERSATILITY

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6.5 base wrap around lens
Parts	Polycarbonate	Secured with lens with screws
Nose Piece	Polycarbonate	Soft nose pad slips on hard nose piece, universal fit
	TPE	
Temple	Polycarbonate	Rotatable temple type, co-injected soft temple tips for comfort
Temple Tip	TPE	
Screw	Stainless steel	Standard hinge screw
Hinge	Polycarbonate	3 barrel type

PART	LENS	LENS MARKING	FRAME MARKING
SB7810S	 Clear	P Z87 + U6	P Z87 +
SB7820S	 Gray	P Z87 + U6 L2.5	P Z87 +
SB7830S	 Amber	P Z87 + S	P Z87 +
SB7870S	 Silver Mirror	P Z87 + S	P Z87 +
SB7880S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact