

Stonewall®

Wrap-Around, Sunglass Style



Black Frame

Part	Lens
VGSB418T ●●●	Bronze Anti-Fog
VGSB422T ●●●	Forest Gray Anti-Fog
VGSB465T ●●●	Ice Blue Mirror Anti-Fog
VGSB470T ●●●	Silver Mirror Anti-Fog





- Built-in rubber nosepiece.
- Wrap-around, sunglass style.
- Durable, flexible nylon frame and straight-back temples.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

GENERAL SPECIFICATION
Bridge: 14mm
Closest Point Between Lens: 10mm
Closest Point Between Temple Tips: 90 +/-5mm
Lens Base: 8 Curve
Lens Size Diagonal: 70mm
Lens Size Vertical: 40mm
Lens Thickness: 2.0mm
Overall Length (Lens-Tip): 136mm
Overall Width (Hinge-Hinge): 134 +/-1mm
Weight: 28g

PACKAGING

Sold individually in a Venture Gear Tactical branded box
Case: 60 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve
Frame	Nylon	Wrap around design with side temples
Temple	PC	Lightweight & comfort-fit
Temple tip	TPR	
Nose Piece	TPR	Comfort-fit
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB418T	 Bronze Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB422T	 Forest Gray Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB465T	 Ice Blue Mirror Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB470T	 Silver Mirror Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark
Z87: ANSI standard for Eye and Face protection devices
+: High Impact
H: Small Head Size
S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
U4: Max Effective Far UV= .04% / Max Near UV= .5%
U5: Max Effective Far UV= .02% / Max Near UV= .2%
U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
L1.7: 55% Max. Visible Light
L2.5: 29% Max. Visible Light
L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
Z87: ANSI standard for Eye and Face protection devices
+: High Impact
P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices